

**TOWNSHIP OF EVESHAM**  
**BURLINGTON COUNTY, NEW JERSEY**

**NOTICE TO BID**

**SEALED BIDS WILL BE RECEIVED BY THE TOWNSHIP OF EVESHAM FOR:**

**2026 NEW AND UNUSED AUTOMATED SIDE LOADING REFUSE TRUCK**

And will be opened and read in public at the Municipal Complex, 984 Tuckerton Road, Marlton, New Jersey on June 18, 2026 at 9:30AM prevailing time in Conference Room "B".

Bid specifications and proposal forms may be obtained from the Township of Evesham, Department of Finance, Municipal Complex, 984 Tuckerton Road, Marlton, New Jersey, Monday through Thursday 8:00 a.m. – 5:30 p.m.

All bids must be accompanied by a certified check, cashier's check or bid bond in the amount of ten percent (10%) of the total lump sum bid, not to exceed \$20,000.00, made payable to the Township of Evesham and be delivered to the place and by the hour above named

Bids must be made on the Township's proposal form and must be enclosed in a sealed envelope bearing the name and address of the bidder and the name "**BID ENCLOSED: AUTOMATED SIDE LOADING REFUSE TRUCK**" on the outside addressed to the Township of Evesham, Office of the Township Clerk, Municipal Complex, 984 Tuckerton Road, Marlton, New Jersey 08053. Bids shall be accepted no later than 9:30 AM at the Township Clerk's office, Room 201. **The bidder shall also provide an exact copy of the bid documents on a USB flash drive in the bid envelope.**

The Township will not assume responsibility for bids mailed in.

The Township reserves the right to accept or reject any or all bids, to waive technical defects and make the award to the bidder most competent to serve the Township's requirements.

Bidders are required to comply with the requirements of N.J.S.A. 10:5-31 et. seq., N.J.S.A. 17:27 (Affirmative Action), P.L. 1963. and Americans with Disabilities Act of 1990 (42 U.S.C. 12101, et.seq.).

REBECCA ANDREWS  
TOWNSHIP CLERK

Township of Evesham

Instructions to Bidders and General Specifications

**For 2026 NEW AND UNUSED AUTOMATED SIDE LOADING REFUSE TRUCK**

1. Sealed bids will be received by the Township of Evesham at 11:00 AM on June 16, 2026, in Conference Room "B" of the Township Municipal Complex, 984 Tuckerton Road, Marlton, New Jersey 08053, at which time said bids will be publicly opened and read aloud for the provision of AUTOMATED SIDE LOADING REFUSE TRUCK as set forth in the specifications attached hereto
2. Bids must be on the proposal sheet furnished by the Township and shall be enclosed in sealed envelope addressed to the Township Clerk, 984 Tuckerton Road, Marlton, NJ 08053 with the front of the envelope marked with the name and address of the bidder and the words "BID ENCLOSED-AUTOMATED SIDE LOADING REFUSE TRUCK". Bids may be mailed or hand delivered and will not be accepted after 11:00 AM at Room 201. **"The bidder shall also provide an exact copy of the bid documents on a USB flash drive in the bid envelope."**
3. All bids must be accompanied by a certified check, cashier's check or bid bond in the amount of ten percent (10%) of the total lump sum bid, not to exceed \$20,000.00, made payable to the Township of Evesham and be delivered to the place and by the hour above named
4. All bidders must complete and forward with the bid a non-collusion affidavit and a corporate disclosure statement setting forth the name and address of all stockholders or partners owning 10% or more stock or interest of the bidder in a corporation or partnership.
5. The Township Council intends to award the contract within 60 days from the receipt of bids and reserves the right to reject any or all bids as may be in the best interest of the Township of Evesham.
6. If the bidder's specifications for furnishing products or equipment are, in any respect, not the equivalent of the detailed Township specifications, this discrepancy must specifically be called to the attention of the Township in the bidder's proposal.
7. Bidders are required to indicate a guaranteed delivery schedule on the Form of Proposal.
8. Unless otherwise specified, the cost of the bid shown shall be the cost to the Township at the delivery point designated which shall be the Township of Evesham Public Works, 100 Sharp Rd., Marlton, New Jersey 08053.
9. The award shall not be binding upon the Township until the contract has been executed by the Township, nor shall any work be performed on account of the proposed contract until the contract has been duly executed and delivered.
10. All bidders shall review with the requirements of "Exhibit A" "Mandatory Affirmative Action Language" N.J.S.A. 10:5-30 through 38 and P.L. 1975, C. 127 (N.J.A.C. 17.27).
11. Only manufactured and farm products of the United States, wherever available shall be used.

12. Within ten (10) days of the date that the Township notifies the successful bidder or bidders of acceptance of the bid, the successful bidder shall execute the contract.
13. All bids shall comply with the requirements of N.J.S.A. 40A:11-1 et seq.
14. If there are any questions regarding the specifications, please contact **David Pfeiffer**, Evesham Township Public Works, at **(856) 983-2798 x6912** or **pfeifferd@evesham-nj.gov**.
15. An executed copy of the manufacturer's service contract and guarantee or warranty shall accompany all bids. The bidder shall supplement this with a written statement of the local maintenance service availability. The service provisions shall set forth the availability of parts and locations of maintenance shops.

**Township of Evesham**  
**BID DOCUMENT CHECKLIST\***

Required by owner	Submission Requirement	Initial each required entry and if required submit the item
<input checked="" type="checkbox"/>	Stockholder Disclosure Certification (For - Profit)	
<input checked="" type="checkbox"/>	Non-Collusion Affidavit	
<input checked="" type="checkbox"/>	Bid Proposal Form	
<input type="checkbox"/>	References	
<input checked="" type="checkbox"/>	Bid Bond (10% of Bid)	
<input checked="" type="checkbox"/>	Exact Copy of the Bid Documents on USB Flash Drive	
<input type="checkbox"/>	Bid Guarantee (with Power of Attorney for full amount of <i>Bid</i> Bond)	
<input type="checkbox"/>	Public Works Contractor Certificate	
<input type="checkbox"/>	Consent of Surety (with Power of Attorney for full amount of Bid Price)	
<input checked="" type="checkbox"/>	Mandatory Affirmative Action Language ( <b>Read Only</b> )	
<input type="checkbox"/>	Prevailing Wage	
<input checked="" type="checkbox"/>	Americans with Disabilities Act of 1990 Language ( <b>Read Only</b> )	
<input checked="" type="checkbox"/>	Proof of Business Registration	
<input checked="" type="checkbox"/>	Investment in Iran and Russia Belarus Disclosure Forms	
<input checked="" type="checkbox"/>	W-9	

\*This form need not be submitted. It is provided for bidder's use in assuring compliance with all required documentation.

**STOCKHOLDER DISCLOSURE CERTIFICATION**

**N.J.S.A 52:25-24.2 (P.L. 1977 c33)**

Failure of the bidder/respondent to submit the required information is cause for automatic rejection

**Legal Name of Bidder:** \_\_\_\_\_

- I certify that the list below contains the names and home addresses of all stockholders holding 10% or more of the issued and outstanding stock of the undersigned.
- I certify that no one stockholder owns 10% or more of the issued and outstanding stock of the undersigned.

**Check the box that represents the type of business organization:**

- Partnership       Corporation       Sole Proprietorship
- Limited Partnership    Limited Liability Corporation       Limited Liability Partnership
- Subchapter S Corporation

Complete if the bidder/respondent is one of the 3 types of Corporations:

Date Incorporated: \_\_\_\_\_ Where Incorporated: \_\_\_\_\_

**Business Address:**

<b>Street Address</b>	<b>City</b>	<b>State</b>	<b>Zip</b>
<b>Telephone #</b>	<b>Fax #</b>		

Listed below are the names and addresses of all stockholders, partners or individuals who own ten (10) percent or more of its stock of ay classes, or who owns ten (10) percent or greater interest therein. Sign and notarize the form below, and, if necessary, complete the stockholder list below.

Stockholders:

Name: \_\_\_\_\_ Name: \_\_\_\_\_

Home Address: \_\_\_\_\_ Home Address: \_\_\_\_\_

Name: \_\_\_\_\_ Name: \_\_\_\_\_

Home Address: \_\_\_\_\_ Home Address: \_\_\_\_\_

Subscribed and sworn before me this \_\_\_\_ day of \_\_\_\_\_, 2 \_\_. \_\_\_\_\_ (Affiant)

(Notary Public)

My Commission expires:

\_\_\_\_\_  
(Print name & title of affiant)  
(Corporate Seal)

**NON-COLLUSION AFFIDAVIT**

I, \_\_\_\_\_ of the City of \_\_\_\_\_ in the County of \_\_\_\_\_, and State of \_\_\_\_\_ of full age, being duly sworn according to law on my oath depose and say that:

I am \_\_\_\_\_ of the firm of \_\_\_\_\_ the vendor making the Proposal for the above named project, and that I executed the said Proposal with full authority so to do; that said vendor has not, directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free, competitive bidding in connection with the above named project; and that all statements contained in said Proposal and in this affidavit are true and correct, and made with full knowledge that the Township relies upon the truth of the statements contained in said Proposal and in the statements contained in this affidavit in awarding the contract for said project.

I further warrant that no person or selling agency has been employed or retained to solicit or secure such contract upon an agreement of understanding for a commission, percentage, brokerage or contingent fee, except bonafide employees or bonafide established commercial or selling agencies maintained by \_\_\_\_\_  
(Name of Contractor) (N.J.S.A. § 52:34-15).

\_\_\_\_\_  
*Print name of affiant under signature*

Subscribed and sworn to before me  
this \_\_\_ day of \_\_\_\_\_, 20\_\_\_.

\_\_\_\_\_  
Notary Public of \_\_\_\_\_

My commission expires \_\_\_\_\_

**FORM OF PROPOSAL**

In compliance with the foregoing invitation for bids, and subject to all the conditions thereof, the undersigned offers and agrees, after having carefully examined the specifications, if this bid be accepted within a reasonable time from the date of the opening, to furnish any or all the items upon which prices are quoted, in accordance with the specifications applying, at the price set opposite each item.

The Legal Advertisement, Instructions to Bidders & General Specifications and Specifications and Plans applying form a part of this proposal.

Delivery, to destination as shown, on any or all of the items, to be completed within \_\_\_\_\_ days from receipt of order.

**IMPORTANT: AS DELIVERY MAY BE A DECIDING FACTOR IN THE AWARD OF AN ORDER OF CONTRACT, IT IS IMPORTANT THAT BIDDERS FURNISH THE INFORMATION REQUESTED ABOVE.**

The undersigned is a Partnership ( )  
Corporation ( )  
Individual ( ) under the laws of the State  
Of \_\_\_\_\_ having principal offices at:

Name of Company: \_\_\_\_\_

Address: \_\_\_\_\_

Dated: \_\_\_\_\_

Signature(s) and title(s) of person(s) authorized to sign.

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**IMPORTANT: A MEMBER OF FIRM OR A PERSON AUTHORIZED TO SIGN BIDS FOR A CORPORATION MUST SIGN PROPOSAL.**

EXHIBIT A

MANDATORY EQUAL EMPLOYMENT OPPORTUNITY LANGUAGE  
N.J.S.A. 10:5-31 et seq. (P.L. 1975, C. 127)  
N.J.A.C. 17:27

GOODS, PROFESSIONAL SERVICE AND GENERAL SERVICE CONTRACTS

During the performance of this contract, the contractor agrees as follows:

The contractor or subcontractor, where applicable, will not discriminate against any employee or applicant for employment because of age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality or sex. Except with respect to affectional or sexual orientation and gender identity or expression, the contractor will ensure that equal employment opportunity is afforded to such applicants in recruitment and employment, and that employees are treated during employment, without regard to their age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality or sex. Such equal employment opportunity shall include, but not be limited to the following: employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. The contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided by the Public Agency Compliance Officer setting forth provisions of this nondiscrimination clause.

The contractor or subcontractor, where applicable will, in all solicitations or advertisements for employees placed by or on behalf of the contractor, state that all qualified applicants will receive consideration for employment without regard to age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality or sex.

The contractor or subcontractor will send to each labor union, with which it has a collective bargaining agreement, a notice, to be provided by the agency contracting officer, advising the labor union of the contractor's commitments under this chapter and shall post copies of the notice in conspicuous places available to employees and applicants for employment.

The contractor or subcontractor, where applicable, agrees to comply with any regulations promulgated by the Treasurer pursuant to N.J.S.A. 10:5-31 et seq., as amended and supplemented from time to time and the Americans with Disabilities Act.

The contractor or subcontractor agrees to make good faith efforts to meet targeted county employment goals established in accordance with N.J.A.C. 17:27-5.2.

The contractor or subcontractor agrees to inform in writing its appropriate recruitment agencies including, but not limited to, employment agencies, placement bureaus, colleges, universities, and labor unions, that it does not discriminate on the basis of age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality or sex, and that it will discontinue the use of any recruitment agency which engages in direct or indirect discriminatory practices.

The contractor or subcontractor agrees to revise any of its testing procedures, if necessary, to assure that all personnel testing conforms with the principles of job-related testing, as established by the statutes and court decisions of the State of New Jersey and as established by applicable Federal law and applicable Federal court decisions.

In conforming with the targeted employment goals, the contractor or subcontractor agrees to review all procedures relating to transfer, upgrading, downgrading and layoff to ensure that all such actions are taken without regard to age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality or sex, consistent with the statutes and court decisions of the State of New Jersey, and applicable Federal law and applicable Federal court decisions.

The contractor shall submit to the public agency, after notification of award but prior to execution of a goods and services contract, one of the following three documents:

Letter of Federal Affirmative Action Plan Approval

Certificate of Employee Information Report

Employee Information Report Form AA302 (electronically provided by the Division and distributed to the public agency through the Division's website at [www.state.nj.us/treasury/contract\\_compliance](http://www.state.nj.us/treasury/contract_compliance))

The contractor and its subcontractors shall furnish such reports or other documents to the Division of Public Contracts Equal Employment Opportunity Compliance as may be requested by the office from time to time in order to carry out the purposes of these regulations, and public agencies shall furnish such information as may be requested by the Division of Public Contracts Equal Employment Opportunity Compliance for conducting a compliance investigation pursuant to Subchapter 10 of the Administrative Code at N.J.A.C. 17:27.

**APPENDIX A**  
**AMERICANS WITH DISABILITIES ACT OF 1990**  
**Equal Opportunity for Individuals with Disability**

The contractor and the Township of Evesham, (hereafter "owner") do hereby agree that the provisions of Title 11 of the Americans With Disabilities Act of 1990 (the "Act") (42 U.S.C. S121 01 et seq.), which prohibits discrimination on the basis of disability by public entities in all services, programs, and activities provided or made available by public entities, and the rules and regulations promulgated pursuant there unto, are made a part of this contract. In providing any aid, benefit, or service on behalf of the owner pursuant to this contract, the contractor agrees that the performance shall be in strict compliance with the Act. In the event that the contractor, its agents, servants, employees, or subcontractors violate or are alleged to have violated the Act during the performance of this contract, the contractor shall defend the owner in any action or administrative proceeding commenced pursuant to this Act. The contractor shall indemnify, protect, and save harmless the owner, its agents, servants, and employees from and against any and all suits, claims, losses, demands, or damages, of whatever kind or nature arising out of or claimed to arise out of the alleged violation. The contractor shall, at its own expense, appear, defend, and pay any and all charges for legal services and any and all costs and other expenses arising from such action or administrative proceeding or incurred in connection therewith. In any and all complaints brought pursuant to the owner's grievance procedure, the contractor agrees to abide by any decision of the owner which is rendered pursuant to said grievance procedure. If any action or administrative proceeding results in an award of damages against the owner, or if the owner incurs any expense to cure a violation of the ADA which has been brought pursuant to its grievance procedure, the contractor shall satisfy and discharge the same at its own expense.

The owner shall, as soon as practicable after a claim has been made against it, give written notice thereof to the contractor along with full and complete particulars of the claim. If any action or administrative proceeding is brought against the owner or any of its agents, servants, and employees, the *owner shall* expeditiously forward or have forwarded to the contractor every demand, complaint, notice, summons, pleading, or other process received by the owner or its representatives.

It is expressly agreed and understood that any approval by the owner of the services provided by the contractor pursuant to this contract will not relieve the contractor of the obligation to comply with the Act and to defend, indemnify, protect, and save harmless the owner pursuant to this paragraph.

It is further agreed and understood that the owner assumes no obligation to indemnify or save harmless the contractor, its agents, servants, employees and subcontractors for any claim which may arise out of their performance of this Agreement. Furthermore, the contractor expressly understands and agrees that the provisions of this indemnification clause shall in no way limit the contractor's obligations assumed in this Agreement, nor shall they be construed to relieve the contractor from any liability, nor preclude the owner from taking any other actions available to it under any other provisions of the Agreement or otherwise at law.

**PROOF OF BUSINESS REGISTRATION:** N.J.S.A. 52:32-44 requires that each bidder (contractor) submit proof of business registration with the bid proposal. Proof of registration shall be a copy of the bidder's Business Registration Certificate (BRC). A BRC is obtained from the New Jersey Division of Revenue. Information on obtaining a BRC is available on the internet at [www.nj.gov/njbgs](http://www.nj.gov/njbgs) or by phone at (609) 292-1730. N.J.S.A. 52:32-44 imposes the following requirements on contractors and all subcontractors that **knowingly** provide goods or perform services for a contractor fulfilling this contract:

- 1). The contractor shall provide written notice to its subcontractors and suppliers to submit proof of business registration to the contractor;
- 2). Prior to receipt of final payment from a contracting agency, a contractor must submit to the contracting agency an accurate list of all subcontractors or attest that none were used.
- 3). During the term of this contract, the contractor and its affiliates shall collect and remit, and shall notify all subcontractors and their affiliates that they must collect and remit to the Director, New Jersey Division of Taxation, the use tax due pursuant to the Sales and Use Tax Act, (N.J.S.A.54:32B-1 et seq.) on all sales of tangible personal property delivered into this State.

A contractor, subcontractor or supplier who fails to provide proof of business registration or provides false business registration information shall be liable to a penalty of \$25 for each day of violation, not to exceed \$50,000 for each business registration not properly provided or maintained under a contract with a contracting agency. Information on the law and its requirements is available by calling (609) 292-9292. A sample of acceptable forms of business registration certificates is provided with these specifications.



# DISCLOSURE OF INVESTMENT ACTIVITIES IN IRAN FORM

STATE OF NEW JERSEY  
DEPARTMENT OF THE TREASURY - DIVISION OF PURCHASE AND PROPERTY  
33 WEST STATE STREET, P.O. BOX 230 TRENTON, NEW JERSEY 08625-0230

BID SOLICITATION # AND TITLE: \_\_\_\_\_

VENDOR NAME: \_\_\_\_\_

Pursuant to N.J.S.A. 52:32-57, et seq. (P.L. 2012, c.25 and P.L. 2021, c.4) any person or entity that submits a bid or proposal or otherwise proposes to enter into or renew a contract must certify that neither the person nor entity, nor any of its parents, subsidiaries, or affiliates, is identified on the New Jersey Department of the Treasury's Chapter 25 List as a person or entity engaged in investment activities in Iran. The Chapter 25 list is found on the Division's website at <https://www.state.nj.us/treasury/purchase/pdf/Chapter25List.pdf>. Vendors/Bidders must review this list prior to completing the below certification. If the Director of the Division of Purchase and Property finds a person or entity to be in violation of the law, s/he shall take action as may be appropriate and provided by law, rule or contract, including but not limited to, imposing sanctions, seeking compliance, recovering damages, declaring the party in default and seeking debarment or suspension of the party.

### CHECK THE APPROPRIATE BOX

I certify, pursuant to N.J.S.A. 52:32-57, et seq. (P.L. 2012, c.25 and P.L. 2021, c.4), that neither the Vendor/Bidder listed above nor any of its parents, subsidiaries, or affiliates is listed on the New Jersey Department of the Treasury's Chapter 25 List of entities determined to be engaged in prohibited activities in Iran.

OR

I am unable to certify as above because the Vendor/Bidder and/or one or more of its parents, subsidiaries, or affiliates is listed on the New Jersey Department of the Treasury's Chapter 25 List. I will provide a detailed, accurate and precise description of the activities of the Vendor/Bidder, or one of its parents, subsidiaries or affiliates, has engaged in regarding investment activities in Iran by completing the information requested below.

Entity Engaged in Investment Activities  
Relationship to Vendor/ Bidder  
Description of Activities

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Duration of Engagement  
Anticipated Cessation Date

\_\_\_\_\_  
\_\_\_\_\_

*\*Attach Additional Sheets If Necessary.*

### CERTIFICATION

I, the undersigned, certify that I am authorized to execute this certification on behalf of the Vendor, that the foregoing information and any attachments hereto, to the best of my knowledge are true and complete. I acknowledge that the State of New Jersey is relying on the information contained herein, and that the Vendor is under a continuing obligation from the date of this certification through the completion of any contract(s) with the State to notify the State in writing of any changes to the information contained herein; that I am aware that it is a criminal offense to make a false statement or misrepresentation in this certification. If I do so, I may be subject to criminal prosecution under the law, and it will constitute a material breach of my contract(s) with the State, permitting the State to declare any contract(s) resulting from this certification void and unenforceable.

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Date

\_\_\_\_\_  
Print Name and Title



## CERTIFICATION OF NON-INVOLVEMENT IN PROHIBITED ACTIVITIES IN RUSSIA OR BELARUS

Pursuant to N.J.S.A. 52:32-60.1, et seq. (L. 2022, c. 3) any person or entity (hereinafter "Vendor") that seeks to enter into or renew a contract with a State agency for the provision of goods or services, or the purchase of bonds or other obligations, must complete the certification below indicating whether or not the Vendor is identified on the Office of Foreign Assets Control (OFAC) Specially Designated Nationals and Blocked Persons list, available here: <https://sanctionssearch.ofac.treas.gov/>. If the Department of the Treasury finds that a Vendor has made a certification in violation of the law, it shall take any action as may be appropriate and provided by law, rule or contract, including but not limited to, imposing sanctions, seeking compliance, recovering damages, declaring the party in default and seeking debarment or suspension of the party.

I, the undersigned, certify that I have read the definition of "Vendor" below, and have reviewed the Office of Foreign Assets Control (OFAC) Specially Designated Nationals and Blocked Persons list, and having done so certify:

*(Check the Appropriate Box)*

A. That the Vendor is not identified on the OFAC Specially Designated Nationals and Blocked Persons list on account of activity related to Russia and/or Belarus.

**OR**

B. That I am unable to certify as to "A" above, because the Vendor is identified on the OFAC Specially Designated Nationals and Blocked Persons list on account of activity related to Russia and/or Belarus.

**OR**

C. That I am unable to certify as to "A" above, because the Vendor is identified on the OFAC Specially Designated Nationals and Blocked Persons list. However, the Vendor is engaged in activity related to Russia and/or Belarus consistent with federal law, regulation, license or exemption. A detailed description of how the Vendor's activity related to Russia and/or Belarus is consistent with federal law is set forth below.

---

---

---

---

---

---

---

---

*(Attach Additional Sheets If Necessary.)*

Signature of Vendor's Authorized Representative	Date
Print Name and Title of Vendor's Authorized Representative	Vendor's FEIN
Vendor's Name	Vendor's Phone Number
Vendor's Address (Street Address)	Vendor's Fax Number
Vendor's Address (City/State/Zip Code)	Vendor's Email Address

<sup>1</sup> Vendor means: (1) A natural person, corporation, company, limited partnership, limited liability partnership, limited liability company, business association, sole proprietorship, joint venture, partnership, society, trust, or any other nongovernmental entity, organization, or group; (2) Any governmental entity or instrumentality of a government, including a multilateral development institution, as defined in Section 1701(c)(3) of the International Financial Institutions Act, 22 U.S.C. 262r(c)(3); or (3) Any parent, successor, subunit, direct or indirect subsidiary, or any entity under common ownership or control with, any entity described in paragraph (1) or (2).

# Request for Taxpayer Identification Number and Certification

Go to [www.irs.gov/FormW9](http://www.irs.gov/FormW9) for instructions and the latest information.

**Give form to the  
 requester. Do not  
 send to the IRS.**

**Before you begin.** For guidance related to the purpose of Form W-9, see *Purpose of Form*, below.

<b>Print or type. See Specific Instructions on page 3.</b>	<b>1</b>	Name of entity/individual. An entry is required. (For a sole proprietor or disregarded entity, enter the owner's name on line 1, and enter the business/disregarded entity's name on line 2.)		
	<b>2</b>	Business name/disregarded entity name, if different from above.		
	<b>3a</b>	Check the appropriate box for federal tax classification of the entity/individual whose name is entered on line 1. Check only one of the following seven boxes.		<b>4</b> Exemptions (codes apply only to certain entities, not individuals; see instructions on page 3):  Exempt payee code (if any) _____  Exemption from Foreign Account Tax Compliance Act (FATCA) reporting code (if any) _____  <i>(Applies to accounts maintained outside the United States.)</i>
		<input type="checkbox"/> Individual/sole proprietor <input type="checkbox"/> C corporation <input type="checkbox"/> S corporation <input type="checkbox"/> Partnership <input type="checkbox"/> Trust/estate  <input type="checkbox"/> LLC. Enter the tax classification (C = C corporation, S = S corporation, P = Partnership) . . . . . <b>Note:</b> Check the "LLC" box above and, in the entry space, enter the appropriate code (C, S, or P) for the tax classification of the LLC, unless it is a disregarded entity. A disregarded entity should instead check the appropriate box for the tax classification of its owner.  <input type="checkbox"/> Other (see instructions) _____		
	<b>3b</b>	If on line 3a you checked "Partnership" or "Trust/estate," or checked "LLC" and entered "P" as its tax classification, and you are providing this form to a partnership, trust, or estate in which you have an ownership interest, check this box if you have any foreign partners, owners, or beneficiaries. See Instructions . . . . . <input type="checkbox"/>		
	<b>5</b>	Address (number, street, and apt. or suite no.). See instructions.		Requester's name and address (optional)
	<b>6</b>	City, state, and ZIP code		
<b>7</b>	List account number(s) here (optional)			

## Part I Taxpayer Identification Number (TIN)

Enter your TIN in the appropriate box. The TIN provided must match the name given on line 1 to avoid backup withholding. For individuals, this is generally your social security number (SSN). However, for a resident alien, sole proprietor, or disregarded entity, see the instructions for Part I, later. For other entities, it is your employer identification number (EIN). If you do not have a number, see *How to get a TIN*, later.

**Note:** If the account is in more than one name, see the instructions for line 1. See also *What Name and Number To Give the Requester* for guidelines on whose number to enter.

<b>Social security number</b>											
				-			-				
<b>or</b>											
<b>Employer identification number</b>											
				-							

## Part II Certification

Under penalties of perjury, I certify that:

1. The number shown on this form is my correct taxpayer identification number (or I am waiting for a number to be issued to me); and
2. I am not subject to backup withholding because (a) I am exempt from backup withholding, or (b) I have not been notified by the Internal Revenue Service (IRS) that I am subject to backup withholding as a result of a failure to report all interest or dividends, or (c) the IRS has notified me that I am no longer subject to backup withholding; and
3. I am a U.S. citizen or other U.S. person (defined below); and
4. The FATCA code(s) entered on this form (if any) indicating that I am exempt from FATCA reporting is correct.

**Certification instructions.** You must cross out item 2 above if you have been notified by the IRS that you are currently subject to backup withholding because you have failed to report all interest and dividends on your tax return. For real estate transactions, item 2 does not apply. For mortgage interest paid, acquisition or abandonment of secured property, cancellation of debt, contributions to an individual retirement arrangement (IRA), and, generally, payments other than interest and dividends, you are not required to sign the certification, but you must provide your correct TIN. See the instructions for Part II, later.

<b>Sign Here</b>	Signature of U.S. person	Date
------------------	--------------------------	------

## General Instructions

Section references are to the Internal Revenue Code unless otherwise noted.

**Future developments.** For the latest information about developments related to Form W-9 and its instructions, such as legislation enacted after they were published, go to [www.irs.gov/FormW9](http://www.irs.gov/FormW9).

### What's New

Line 3a has been modified to clarify how a disregarded entity completes this line. An LLC that is a disregarded entity should check the appropriate box for the tax classification of its owner. Otherwise, it should check the "LLC" box and enter its appropriate tax classification.

New line 3b has been added to this form. A flow-through entity is required to complete this line to indicate that it has direct or indirect foreign partners, owners, or beneficiaries when it provides the Form W-9 to another flow-through entity in which it has an ownership interest. This change is intended to provide a flow-through entity with information regarding the status of its indirect foreign partners, owners, or beneficiaries, so that it can satisfy any applicable reporting requirements. For example, a partnership that has any indirect foreign partners may be required to complete Schedules K-2 and K-3. See the Partnership Instructions for Schedules K-2 and K-3 (Form 1065).

### Purpose of Form

An individual or entity (Form W-9 requester) who is required to file an information return with the IRS is giving you this form because they

**TOWNSHIP OF EVESHAM  
SPECIFICATIONS FOR 2026 OR CURRENT MODEL YEAR  
NEW AND UNUSED AUTOMATED SIDE LOADING REFUSE TRUCK**

The specifications contained herein are intended to describe an automated side loading high compaction refuse truck to be used by the Evesham public works department. It must be designed and constructed for efficient collection of industry recognized residential and light commercial 95 and 65 gallon wheeled automated refuse carts.

The bidder will submit a binding proposal on the forms accompanying these specifications, in the manner indicated in the notice to bidders. The bid shall be submitted in a sealed envelope with the words **“bid enclosed-automated side loading refuse truck”**.

Complete unit(s) ready for use, shall be delivered to the township no more than 365 calendar days from the signing of a contract. In the event a multiple truck bid is awarded, all units must be manufactured the same per specifications. Unlike units in a multiple truck award will not be accepted.

The bidder shall guarantee that all articles of equipment including all parts thereof are of first quality throughout. The bidder further warrants, per specifications, all equipment and all parts thereof against any defects of workmanship, design, construction and materials, and guarantees to repair or replace without cost of the owner, any article that has become defective, in service and not proven to have been caused by negligence on the part of the user.

If requested, bidder must provide a working demo either prior to the bid date or within 5 days after the bid date to be eligible for an award of the contract. Demo unit must be a similar unit to the specified truck(s) to qualify as a demo for this bid.

There shall be a 20-working day trial period for each vehicle, during which time the vehicle will be used, prior to final acceptance of the vehicle by the township. During this 20-day period, the bidder shall immediately remedy any and all faults in the new vehicle(s) brought to the bidder's attention by the township. In the event a multiple truck bid is awarded the bidder may be requested by the township of Evesham to deliver one (1) or the first unit independent of the remaining units to be used during the 20-day trial period as described above. After acceptance of the first unit the bidder will then get approval to deliver the remaining units.

All items required to make a complete, finished, working unit must be included whether specified or not. If a bidder has questions about the specifications, the questions may be addressed to: Evesham public works, 984 Tuckerton rd. Marlton, NJ 08053 or by calling 856-983-2798.

Payment will be in a lump sum following acceptance of the vehicle(s) by the township. Payment will be made within thirty (30) days of when the bidder presents a voucher for payment. The voucher may be submitted upon acceptance of the vehicle(s) by the township.

Warranty service will be the responsibility of the successful bidder, if service is required during the warranty period, the supplying vendor is responsible for the pick-up and delivery of the vehicle and any parts or service required to make the necessary repairs.

The complete unit, chassis, body and associated equipment, must have a local factory authorized facility for all parts and service. If requested, bidders must provide proof and any requested information about the location(s). Local shall be defined as within 40 miles from the Evesham public works facility.

Unless noted, explained and approved prior to the bid opening: the specified items are to be provided exactly as described. If no exception is taken, the word **none** must be written in the exception field or next to the technical description. The terms approval equal apply to the truck, all mounted equipment, parts, performance, documentation, training and accessories. Equal or better will be judged by the end user (Evesham Public Works). If a bidder declares that an item is equal or better; they are required to provide demonstrations, written explanations, comparisons, as well as written technical and performance data with quantified, verifiable conclusions to support their claim. Failure to submit the complete information prior to the bid opening will result in the immediate rejection of the entire bid. The Township

reserves the right to waive any informality in, or to reject any or all bids in accordance with N.J.S.A. 40:A-11-13.2, and to award contracts in whole or in part, if deemed in the best interest of the Township to do so.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_\_ **NO** \_\_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

### **SPECIFICATION - LOW CAB FORWARD RIGHT HAND DRIVE ONLY CHASSIS**

#### **GENERAL**

It is the intent of these specifications to describe a chassis and cab combination with a minimum GVW of 66,000 LBS., fully equipped and road ready, easily capable of transporting over the road and in landfills, a fully packed – 33- cu. yard (body & tailgate) automated collection system as described herein. The equipment to be supplied shall be new and unused and shall be manufacturer’s 2026 or current year production model, including accessories and normally standard features not specifically mentions but normally supplied and/or necessary to furnish a unit complete and ready for operation.

It must be understood that the chassis supplier and the body supplier must confirm that the specifications for the chassis, body and related mounted equipment are correct, compatible and will provide a complete working unit operating as intended. Any questions or concerns pertaining to the specifications must be brought to the attention of the Evesham Township’s Superintendent of Public Works or the designee.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_\_ **NO** \_\_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

#### **CAB & EQUIPMENT**

The cab shall be a low cab forward design. Includes steel frames with alum and fiberglass panels, all alum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, full insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, pull down windshield sunshade, 16in steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls, rear cab corner windows, 18in bolt-on step on each side, self-canceling turn signals and Front Directional and Side Mounted Turn Signals.

- Thermal insulation shall cover the underside of the engine tunnel.
- Self-cleaning stainless-steel steps shall be provided on both sides of cab.
- Doors to have flush mounted paddle style door handles.
- External sun visor – Stainless steel – OEM installed.
- All glass to be tinted – windshield – 2 piece.
- Power Windows – Both Doors
- Rear window to be one piece, stationary with standard tint.
- Unit to have a wet arm windshield washer with washer bottle located inside passenger side of cab.
- Unit to have Single Rectangular halogen headlamps with high/low beam switch in turn signal stalk mounted on steering column.
- Insulated Rubber floor mats. Back panel to be heavy duty vinyl.
- Cab to tilted via hydraulic tilt mechanism allowing for a minimum of 65-degree cab tilt angle.
- Cab to be right-hand drive only.
- Cab exterior to be equipped with single chrome air horn with shield, chromed LH/RH Tri-plane mirrors, heated, Motorized, Mounted to Doors. Chrome mirror shell / black arms. Dual electric horns. Power windows (Both Doors).
- Cab interior includes ABS gray headliner & rear cab panel, gray vinyl engine tunnel cover.

- A door operated cab dome light shall be provided.
- Cab environmental to include a Combo Fresh Air Heater/Air-Conditioner with radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses. – OEM installed.
- The seating provided shall include a Low-back air suspended vinyl driver's and a static low back passenger seat, both with three-point seat belts.
- Adjustable Tilt/Telescopic Steering wheel shall be provided. Cab entry handles on exterior both sides.
- Unit to be equipped with an air restriction gauge.
- Engine shutdown, with audible and visual alarms, for low air pressure high water temperature and low water level shall be supplied.
- The following instruments and gauges shall be supplied: electronic speedometer and odometer, dual air pressure gauges, engine oil pressure gauge, coolant temperature gauge, fuel level gauge, DEF level gauge, voltmeter, engine oil temperature, rear axle temperature. Electric hour-meter, electric tachometer, transmission temp. gauge.
- The following warning lamps shall be provided: coolant level, coolant temperature, low air pressure, low oil pressure, turn signal indicators and high beam indicator.
- Unit to be supplied with manual reset circuit breakers, seven (5) Clearance lights LED & (2) Marker Lights LED. Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door., front turn signals with chrome housing and turn signal switch non-cancelling type. Parking lights and Daytime running lights.
- Cab to include: Concert Class without CD includes Bluetooth phone & Audio, AM/FM, WB, USB and MP3.
- The cab to be equipped with electric intermittent wipers on both sides.
- Rubber bulb door seals.
- The cab to be painted White.
- A fire extinguisher and a triangle reflector kit to be included.

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_\_ NO \_\_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

### **ENGINE & EQUIPMENT**

Unit to be powered by a PACCAR MX-11 400R 400HP@1600 GV@2200 1450@900 Refuse (2024 EMISSIONS). Includes alum flywheel housing. SAE 15W40 engine oil specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. Engine must be Certified & Compliant.

Engine to be equipped with the following:

- Engine mounted full flow oil filter and by-pass oil filter.
- Engine dipstick located behind cab for daily routine check w/o lifting cab.
- 25.9 CFM Air compressor.
- A/C compressor.
- Fuel cooler.
- On/Off Fan clutch – automatic.
- HD Air Cleaner w/molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.
- Silicone radiator and heater hoses.
- Anti-freeze protection to (-30F) and Extended life coolant.
- High efficiency cooling system radiator with coolant fill & check back of cab – for daily routine check w/o tilting cab.
- 12 Volt Starter
- 160 AMP Alternator brushed.
- Three (3) 12V Dual Purpose Maintenance free 2190 CCA batteries. Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.
- Heated Fuel Filter.

- Single vertical exhaust stainless steel.
- C-Brake - MX Jacobs (Engine Brake)

**COMPLY WITH SPECIFICATIONS:**      YES \_\_\_\_ NO \_\_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**TRANSMISSION**

- Transmission to be an Allison 4500RDS-P wide ratio, (6) speed automatic.
- Driveline 1810HD with a single mid-ship bearing.
- TranSynd Automatic Transmission fluid.
- Allison RDS Auto Neutral 'AK'
- Provisions for PTO (unit will have a transmission mounted PTO driven hydraulic pump)

**COMPLY WITH SPECIFICATIONS:**      YES \_\_\_\_ NO \_\_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**FRONT AXLE**

- The front axle to be a Dana Spicer 20,000 lb. capacity or equal.
- Wide Track Front Axle. For improved turning radius.
- Power steering Sheppard SD110 Dual.
- Nine (9) quart power steering reservoir. Remote mounted for daily routine check w/o tilting cab.
- 20,000 lb. Taper leaf springs with shocks.
- Iron Pre-set Plus Hubs
- Drum Air Brakes – front axle
- Oil seals.

**COMPLY WITH SPECIFICATIONS:**      YES \_\_\_\_ NO \_\_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**REAR AXLE**

- The rear axle to be a Dana Spicer D46-172P 46,000 lb. capacity, or equal, with Bendix Smart ATC Traction Control and differential locks, both axles.
- Hendrickson RT 46,000 lb. capacity suspension. 54" AS. Shock Absorbers.
- Drum Air Brakes, Tandem Axle.
- Four (6) parking brake chambers. Bendix ABS, full traction control.
- Automatic Slack Adjusters.
- Oil seals.
- Synthetic Axle lubricant.

**COMPLY WITH SPECIFICATIONS:**      YES \_\_\_\_ NO \_\_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**FRAME**

- The frame to be 10.75"x3.5"x .375" with a full steel frame liner. RBM to be a minimum of 3,468,000 with all bolts huck fastened. Zinc-coated anti-corrosion treated frame rails.

- Wheelbase 221". Must be optimum measurement to accommodate body selection. Chassis and body suppliers must coordinate and confirm the appropriate wheelbase. Notice must be made if changes to the specification are needed.
- Bendix AD-ISEP air dryer with heater. Extended Purge (for use with higher consumption applications). Includes Single-Bolt Dessicant Cartridge and wet Air Tank.
- 80-gallon Aluminum fuel tank 26", mounted LH Frame. Shut-off valve at the tank.
- SAE J844 nylon tubing fuel lines or wire braid fuel lines.
- Aluminum battery box left hand mounted with shut off switch & battery jumper terminals mounted in front of battery box.
- Electrical back up alarm – body builders junction box – all electrical wires and air lines routed through cross members protected by convoluted tubing.
- Painted steel front bumper – heavy duty.
- Two (2) front removable tow pins.
- Steel air tanks located inside frame rail.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**TIRES & WHEELS**

- Shall have two (2) front tires to be Bridgestone (or equivalent) M860A 315/80R 22.5" 20 ply.
- Shall have eight (8) rear tires to be Bridgestone (or equivalent) M843 11R 22.5" 16 ply.
- Front wheel shall be 22.5 x 9.00" ACCUR 29039 HD steel hub pilot painted white. Rear wheel shall be 22.5 x 8.25" ACCUR 50291 HD steel hub pilot painted white.
- One (1) spare front tire and wheel and one (1) spare rear tire and wheel to match.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**MISCELLANEOUS**

- Dry type 5 lb. fire extinguisher.
- Flare kit with three (3) triangular reflectors.
- One (1) complete set of Parts & Service manuals. Electronic version acceptable.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**PAINT**

- Paint - cab exterior, single color, white (high gloss)
- Paint - cab, urethane clear coat
- Paint - chassis running gear, black (urethane)
- Paint - bumper, same as chassis running gear
- Front wheels pre-finished white
- Rear wheels pre-finished white

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**WARRANTY**

- Transmission: 3 year/unlimited mileage – 100% parts and labor.
- Engine: Five Years/100,000 Miles. Coverage is 100 percent parts and labor with no deductibles on internally lubricated components and major engine systems including turbo charger, water pump, and fuel injectors.
- All other components warranted for a minimum of one (1) year from delivery date.
- Aftertreatment Coverage: Five Years/100,000 Miles. Coverage is 100 percent parts and labor with no deductibles on the DEF controller / dosing unit / dosing valve, SCR catalyst, catalytic converter particulate filter, SCR/DPF temperature sensor interface module, and other related aftertreatment parts

If the warranty facility is located outside a forty (40) mile radius of the Evesham Township Public Works Garage, the successful bidder shall be required to transport the vehicle for any warranty work.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**EVESHAM TOWNSHIP  
SPECIFICATIONS FOR A NEW AND UNUSED 2026 OR CURRENT MODEL YEAR  
AUTOMATED SIDE LOADING HIGH COMPACTION BODY WITH MECHANIZED LOADING ARM**

It is the intent of these specifications to describe the minimum requirements for a complete working side loading high compaction body with mechanized loading arm.

The complete body with arm and all associated equipment shall be installed on specified chassis to provide a complete working unit.

The body installer, if separate from the chassis supplier, must provide the chassis supplier with all needed information and/or requirements to properly complete a working unit.

The omission of any standard feature description shall not alleviate the bidder from the responsibility of furnishing a complete body with all standard equipment of the manufacturer’s latest improved model in current production as offered to commercial trade. The body shall conform in strength, quality of material, workmanship and provided the best manufacturing and engineering practices of the industry.

It is required that the units, as specified herein, shall be completely assembled and adjusted and that all equipment, including standard and optional equipment, be installed on a chassis furnished by others and the unit made ready for continuous operation.

The bidder shall represent by his bid that all equipment to be furnished under this bid is new and unused.

All bidders shall attach a statement that the unit offered meets these specifications exactly, or list any exceptions fully and accurately.

The Township reserves the right to waive any informality in, or to reject any or all bids in accordance with N.J.S.A. 40:A-11-13.2, and to award contracts in whole or in part, if deemed in the best interest of the Township to do so.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**BODY SPECIFICATIONS AND STANDARDS**

- The body shall be rounded to permit a maximum capacity.
- The minimum capacity of the body shall be, excluding the hopper area, 27 cubic yards.

- The capacity of the tailgate shall be 6 cubic yards.
- The hopper capacity shall be 6.5 cubic yards.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**BODY DIMENSIONS**

- The body shall be tapered to facilitate the unloading of the material and to increase compaction ratio.
- The total taper dimension of the body sides shall be 9.5" (inches).
- The inside body width at front shall be 87-1/2" (inches).
- The inside body width at rear shall be 96" (inches).
- The outside body width shall be 96" (inches).
- The inside body height at the rear shall 92.5 " (inches).
- The overall length including hopper shall be 296" (inches).
- The outside body height above frame without automated arm shall be 103" (inches).
- The overall body height over chassis with automated arm in traveling position shall be 103" (inches).

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**FLOOR CONSTRUCTION**

- The hopper floor shall be made of Abrasion resistant steel.
- The hopper floor steel grade shall be Hardox 450 The entire steel must be treated throughout
- Steel that is treated on the outside only will not be acceptable
- The hopper floor thickness shall be one quarter inch (1/4")
- The hopper floor yield strength shall be 175,000 psi.
- The body floor shall be rounded.
- The body floor thickness shall be 0.157 ‘‘ The body floor steel grade shall be Hardox 450 (or equivalent).
- The body floor yield strength shall be 175,000 psi.
- The body long sills dimensions shall be tube HSS 6" x 2" x 3/8".
- The body long sills yield strength shall be 50,000 psi.
- Hopper sump box volume shall be 30.7 gallon.
- Hopper sump box dimensions shall be 14" x 6" x 87".
- The front part of the body floor will have a 48’’ hardox liner covering entire width of floor.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**SIDE CONSTRUCTION**

- The body walls shall be rounded and smooth, improving resistance and featuring lightness
- One-piece full length of the body to reduce welding seams.
- The upper body walls thickness shall be 12 ga. and lower 10ga
- The body walls steel grade shall be ASTM A-1011 GR 80.
- The body walls yield strength shall be 80,000 psi.
- Hopper lower sides walls thickness shall be 1/4 ‘‘
- Hopper lower sides walls steel grade shall be Hardox 450
- Hopper sides walls yield strength shall be 175,000 psi.
- Front bolster thickness shall be 12 ga.

- Front bolster steel grade shall be ASTM A1011CS.
- Front bolster dimensions shall be 5 13/16 x 5 x 4 3/4” Rear bolster 7x9x813/16 “
- A body window, made of expanded metal is installed on the front wall of the body to indicate when body is full.
- A hopper access door shall be installed to permit the driver to have access to the hopper if something falls off the cart.
- The hopper upper walls part steel grade shall be A-569.
- The hopper upper right wall thickness shall be 10 ga.
- The hopper upper left wall thickness shall be 10 ga.
- The hopper walls lower part steel thickness shall be 1/4".
- The hopper walls lower part steel grade shall be Hardox 450.
- The hopper access door thickness shall be 10 ga.
- The hopper access door steel grade shall be ASTM 1011 CS.
- The hopper access door dimensions shall be 28 5/8 X 44".
- Front bolster steel grade shall be ASTM 1011 CS.
- Front bolster steel thickness shall be 12 ga.
- Front bolster dimensions shall be 5 13/16 X 5 X 4 3/4”.
- Rear bolster steel grade shall be ASTM1101CS
- Rear bolster steel thickness shall be 0.188".
- Rear bolster dimensions shall be 7 X 9 X 8 ".
- A work light shall be installed on side wall to illuminate the automated arm in operation.

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**ROOF CONSTRUCTION**

- Body roof shall be rounded and made of high yield steel to ensure strength when material is packing against it.
- The roof thickness shall be 12 ga.
- The roof steel grade shall be ASTM A1101 GR 80F.
- The roof yield strength shall be 80,000 psi.
- Front bolster steel grade shall be A-569.
- Rear bolster steel thickness shall be 12 ga.
- Rear bolster dimensions shall be 6 5/8 x 6 5/8 x 7 7/16”
- Rear bolster steel grade shall be csa g40.21 50w.
- Rear bolster steel thickness shall be 3/16".

**COMPLY WITH SPECIFICATIONS:**        **YES** \_\_\_ **NO** \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**HOPPER CONSTRUCTION**

- The curbside hopper depth shall be 56".
- The street side hopper depth shall be 70.5".
- The hopper length shall be 69.5".
- The hopper width shall be 66".
- The follower panels stall thickness shall be 3/16”
- The follower panels steel grade shall be AR200.
- Sliding hopper access step with grab handles shall be provided.
- A work light shall be installed in top of the hopper
- Hardox hopper and side wall liner
- The breaker bar will have (6) replaceable retainer teeth 2 1/2” tall to reduce material from falling back into hopper.

COMPLY WITH SPECIFICATIONS: YES \_\_\_ NO \_\_\_

LIST ANY DEVIATIONS: \_\_\_\_\_

### TAILGATE

- The rear tailgate shall be hydraulically operated, bustle type with an automated lock mechanism and hydraulic safety locks.
- 6 Cubic yard capacity
- Tailgate thickness shall be 12 ga.
- The tailgate steel shall be ASTM A1101 GR80F.
- The tailgate yield strength shall be 80,000 psi.
- The tailgate shall be operated by 2 cylinders.
- Tailgate cylinder bore diameter shall be 2-1/2".
- Tailgate cylinder rod diameter shall be 1-3/4".
- Tailgate cylinder stroke shall be 39".
- Tailgate cycle time at idle shall be 55 sec.
- A rubber seal shall be installed on the tailgate to prevent liquid leakage and banging on back of body to a height of 30".
- A cab mounted light and an audible alarm shall be provided to indicate that the tailgate is unlocked.
- A manual control with safety lock shall be installed in the cab to prevent accidental activation.
- Tailgate safety prop shall be provided.
- Tailgate side framing Steel AR 200
- Tailgate top framing shall be 4- x 4" x 3/16 "
- Tailgate bottom framing shall be tube HSS tubing
- Tailgate hydraulic line shall be equipped with flow restrictor to prevent sudden descent of the tailgate.
- Tailgate cylinder pins diameter shall be 1-1/4".
- Tailgate shall be equipped with proximity switches.

COMPLY WITH SPECIFICATIONS: YES \_\_\_ NO \_\_\_

LIST ANY DEVIATIONS: \_\_\_\_\_

### PACKER

- The packer shall be unitized, integral with body and shall be guided by 2 rails. Hardox steel
- The packer shall be 24" high providing 75,400 lbs. of force on material, ensuring efficient packing.
- Rails wear plates shall be made of steel grade Hardox 450.
- Rails wear plates thickness shall be one quarter (1/4").
- Rail dimensions shall be 3-1/2" x 2-3/16".
- Packer wear shoes steel grade shall be Hardox 450.
- Packer wear shoes thickness shall be 3/8".
- Packer shall be operated by 2 cylinders.
- Packer cylinder rods shall be chrome plated.
- Cylinder bore diameter shall be 4".
- Cylinder rod diameter shall be 2-1/2".
- Cylinder stroke shall be 40".
- Maximum operation pressure shall be 3,000 psi.
- Maximum compaction density of refuse shall be 900 lbs.
- Packer cylinder pins diameter shall be 1-3/4".
- Packer cylinder pins steel shall be HR-1045.
- Inside width of packing ram shall be 65.5".
- Inside height of packing ram shall be 24".
- Packing ram stroke shall be 52".

- Packing ram top steel grade shall be CSA G40 .21 100 QT
- Packer to be reinforced with a combination of structural members for maximum rigidity.
- Packing ram structural steel grade shall be A-569.
- Packing ram top thickness shall be one quarter inch (1/4").
- Packing ram top yield strength shall be 100,000 psi.
- Packing face plate steel grade shall be CSA G40.21 100 QT.
- Packing face plate thickness shall be one quarter inch (1/4").
- Packing face plate yield strength shall be 100,000 psi.
- Penetration of the ram into body shall be 6".
- Packer ram cycle time shall be 14 seconds.
- Packer length with following panel shall be 55".
- Packer controls shall consist of start, retract and emergency stop.
- Emergency red button shall be provided to stop packer ram at any time.
- One complete set of packer controls located in cab shall be provided.
- Control buttons shall be heavy duty, industrial type, color coded, corrosion proof and weather resistant.
- The packer cycle shall be programmable, after the grab is activated an automatic packer cycle occur-after a seven (7) second delay.
- The self-compacting module called Grab Pack or equivalent
- The number of complete packer cycles shall be easily adjustable from 2 to 8 cycles. The electronic module shall be called multi-cycle.
- Packer shall be equipped with proximity switches to control the cycle.
- Packer control buttons (except red one) diameter shall be 1-9/16".
- Packer stop button diameter shall be 2-3/4".

**COMPLY WITH SPECIFICATIONS:**      YES \_\_\_\_ NO \_\_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

### **HYDRAULIC SYSTEM**

- Hydraulic system shall be composed of 2 vane pumps with a combination of fixed displacement vane pump for the body functions and a variable piston pump for the arm, pumps shall have a common suction port.
- Hydraulic pump must be transmission mounted.
- Body function shall deliver 20 GPM @ 700 rpm. and arm function 16 GPM @700
- The hydraulic pressure body line shall be made up of a Denison (or equivalent) relief valve R5P, a Denison (or equivalent) vent valve VV01 with a 12 volts DC in line mounted solenoid which divert the flow back to tank when pump is not engaged, and finally a flow control block which divert the excess flow back to tank over: 45 GPM.
- Hydraulic system pressure relief valve for the arm shall be 2100 psi.
- Hydraulic system pressure relief valve for the body shall be 3,000 psi.
- Capacity of hydraulic reservoir shall be 85 gallons.
- Hydraulic reservoir shall be baffled, and pressurized equipped with magnetic drain plug, oil level sight gauge and shut-off valves in suction line.
- The in-tank return line filter capacity shall be 150 GPM.
- Nominal filtration rating shall be 7 microns.
- Filtration ratio per ISO 16889 shall be beta ratio 10/200.
- Suction line strainer size shall be 100 mesh.
- Suction line strainer capacity shall be 100 GPM.
- All hoses shall be double braided wire minimum, high burst capacity and reinforced with nylon wrap to prevent chapping.
- Hydraulic tubing shall be used where flexibility is not needed.
- All pipes shall be zinc coated to prevent corrosion.
- All hydraulic tubing shall be securely clamped to prevent vibration, abrasion and excessive noise.
- All hydraulic hoses shall conform to S.A.E. standards for designed pressure, bends shall not be less than recommended by S.A.E. standards.

- Hydraulic system shall operate at an acceptable temperature without the need for external hydraulic oil cooling devices.
- Quick disconnect fittings shall be provided so that a pressure gauge can be easily connected without the use of tools or the need to remove hydraulic fittings.
- Hydraulic reservoir pressure shall be 5 psi.

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**CART LIFTING MECHANISM "RIGHT HAND" HEAVY DUTY WITH 6X6 CHAIN**

- Arm is attached under the body to ease chassis serviceability and prevent frame damage. Chassis mounted arm assembly will not be accepted
- Arm lift frame yield strength shall be 100,000 psi.
- All cylinders shall be chromed plated in minimum with a spherical bearing at each end.
- Grab clamp shall be actuated by a single hydraulic cylinder and use a high friction rubber strapping.
- Grab assembly shall enable loading roll carts of 32 to 95 U.S. gal.
- Maximum lifting capacity at minimum reach shall be 600 lbs.
- Maximum lifting capacity at maximum reach 600 Lbs.    Two leveling rods ensure stable displacement and rotation above hopper. Rods are adjustable
- The grabber valves shall be on-off type.
- The joystick shall have an on-off rocker switch for the control of the grab.
- An arm rest shall be installed in an adequate location for joystick operation.
- Horizontal reach from side of vehicle to center of cart shall be 0 to 144"(No exception)
- Dump height SHALL NOT EXCEED 108 "
- Unit weight without grab and oil but including valve bank shall be 1,950 tbs.
- Recommended hydraulic pump flow rate for the arm shall be 14 GPM @ 850 rpm.
- Lifting mechanism cycle time at minimum reach shall be 10 seconds.
- Lifting mechanism cycle time at maximum reach shall be 20 seconds.
- Grab operating pressure shall be 1,200 psi.
- Auto dump (automatically dump cart and return it by the side of the truck.

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**BODY LIFTING MECHANISM**

- The hoist cylinder shall be front mounted with outer cover and bottom lifting for greater stability of the tipped body.
- Body shall be raised by one single acting front mounted telescopic cylinder.
- The number of stages in telescopic cylinder shall be four (4).
- Total stroke of body lifting cylinder shall be 180".
- Body cylinder bore diameter shall be 6.5" and cylinder is salt bath nitriding
- Body dump angle shall be 45°.
- Safety prop shall be supplied to support the body in the raised position.

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**ELECTRICAL SYSTEM**

- All stop, directional, tail and clearance lights shall be LED recessed mount and watertight or equivalent.

- All lights shall be provided following FMVSS & CMVSS #108.
- Rear lights to be integrated to tailgate structure.
- Back-up alarm shall be provided.
- All circuits shall be properly fused.
- All wiring shall be color coded and numbered
- All wirings shall be protected with plastic sheath.
- All connections weather pack or equal - no scotch lock type connections.
- Work lights shall be installed: 1 hopper, 1 side/arm.
- Strobe light (1) shall be installed at rear of body.
- Two (2) rear amber alternating flashing lights to be installed top rear of body and front.
- Wire shall conform to SAE J1128.

**COMPLY WITH SPECIFICATIONS:** YES \_\_\_ NO \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**ACCESSORIES**

- Mud guards shall be supplied for both sides of rear axle and mounted on the body tailgate.
- Folding ladder on curb side to access be hopper shall be provided.
- Broom and shovel kit with brackets on body shall be provided.
- Hopper spill shield

**COMPLY WITH SPECIFICATIONS:** YES \_\_\_ NO \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**PAINTING**

- The truck shall be properly cleaned of all dirt, grease and weld slag.
- The body and hopper shall be steel grit blasted.
- One coat of polyurethane primer Imron 5000 (or equivalent) shall be applied.
- Finish paint coat shall be baked.
- The body shall be painted white.
- A rust protection shall be applied in the body cavities.
- Conspicuity tape according to ANSI standards shall be installed on body.
- Automated arm shall be painted safety yellow.

**COMPLY WITH SPECIFICATIONS:** YES \_\_\_ NO \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**MANUALS**

- Parts, service and operator's manual shall be supplied for the refuse packer body and related equipment.

**COMPLY WITH SPECIFICATIONS:** YES \_\_\_ NO \_\_\_

**LIST ANY DEVIATIONS:** \_\_\_\_\_

**LUBRICATION**

- All body hinges, cylinder rod ends, cylinder base trunnions and packer grease fittings shall have easy access outside body.
- Grease chart shall be permanently affixed on the body.

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_  
**LIST ANY DEVIATIONS:** \_\_\_\_\_

**WARRANTY**

- Length of warranty on defective parts shall be two years.
- Length of warranty on hydraulic cylinders and hoses shall be two (2) years.
- Length of warranty on automated arm shall be two (2) year.
- Length of warranty on paint product shall be two (2) years.
- A clear and concise statement of the terms and conditions of the warranty shall be supplied.
- Warranty shall start at the time of in-service date.

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_  
**LIST ANY DEVIATIONS:** \_\_\_\_\_

**MANUFACTURER TRAINING**

- Manufacturer shall supply a Factory Service Representative with the system to conduct a Maintenance and Service School on the equipment, plus operator training

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_  
**LIST ANY DEVIATIONS:** \_\_\_\_\_

**CERTIFICATION**

- The body manufacturer shall be certified ISO 9001.
- All internal inspection documents such as intermediate inspection welding shall conform to the standard CSA-W47.1.
- Body shall form to ANSI Z245.1-1999.

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_  
**LIST ANY DEVIATIONS:** \_\_\_\_\_

**CAMERA SYSTEM**

- A camera system shall be installed, consisting of a minimum 5.5" flat panel, color monitor mounted inside the cab, capable of viewing the hopper at all times; and the rear of the truck while it is backing up & left side mirror.

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_  
**LIST ANY DEVIATIONS:** \_\_\_\_\_

**BODY AIR SYSTEM**

- Remote air drain system

**COMPLY WITH SPECIFICATIONS:**        YES \_\_\_ NO \_\_\_  
**LIST ANY DEVIATIONS:** \_\_\_\_\_

**PROPOSAL PAGE FOR 2026 OR CURRENT MODEL YEAR  
NEW AND UNUSED AUTOMATED SIDE LOADING REFUSE TRUCKS**

The Township reserves the right to award bids in the best interest of the Township. Units shall be complete, checked and in working order delivered to:

**Evesham Public Works  
100 sharp Rd.  
Marlton, NJ 08053**

**BIDDER'S CONTACT INFORMATION**

Company: \_\_\_\_\_  
Contact Person: \_\_\_\_\_  
Address: \_\_\_\_\_  
\_\_\_\_\_  
Phone: \_\_\_\_\_  
Email: \_\_\_\_\_

YEAR, MAKE AND MODEL OF CHASSIS: \_\_\_\_\_

YEAR, MAKE AND MODEL OF REFUSE BODY: \_\_\_\_\_

ANY EXCEPTIONS OR DEVIATIONS FROM SPECIFICATIONS      YES \_\_\_\_\_ NO \_\_\_\_\_

TOTAL PRICE FOR ONE (1) UNIT DELIVERED \$ \_\_\_\_\_